

A & F Wood Products, Inc

5665 Sterling Drive Howell, Michigan 48843
Phone: 517-545-5811 Fax: 517-545-5633 Toll Free: 800-367-3293
www.afwood.com

Machining Specifications Panel 20 Minute Door

HINGES:	Up to 3/0 x 7/0:	4" high x 105 steel, mortised, Surface (labeled self-closing spring type) 4.5" X 134" steel, mortised, surface.
	Over 3/0 x 7/0:	4.5" high x 134" steel mortised, surfaced
LATCHES:	All latch sets shall be listed for use in solid wood core fire doors.	
CYLINDER LOCK:	Maximum bore 2 1/8", maximum backset 2 3/4".	
MORTISE LOCK:	Maximum cut-out of 6 3/4" high by 4 3/4" deep by 1 -1/16" wide (machining depth of body shall not exceed the lock dimension by more than 1/8").	
EXIT DEVICES:	Also known as Rim Locks, Vertical Rods or Panic Hardware available on Commercial only .	
DEADBOLTS:	All deadbolts used shall be listed, have a maximum 2 1/8" bore, and located no closer that 6" centerline to centerline about the latched cut-out.	
FLUSHBOLTS:	Automatic or surface mounted manual type.	
LOUVERS:	Not applicaable	
VISION PANELS:	Not applicable	
VIEWERS:	(2) 1/2" diameter, or (1) 1" viewer (peep sight) not to be located within the profile.	